

REFRIGERATOR MANUFACTURER
Turbo air
 more durable, efficient, beautiful

4184 E. Conant St.
 Long Beach, CA 90808
 Tel. 310-900-1000
 Fax. 310-900-1077
www.turboairinc.com

Project :

Model # :

Item # :

Qty :

Available W/H :

Approval :

Roll-In Solid Door Heated Cabinet

Roll-In
PRO Series

Model : PRO-50H-RI

FEATURES & BENEFITS

■ Digital temperature control & monitor system

- Keep food products safe by maintaining constant temperatures.
- Alarm beeps when doors are not sealed.
- Early warning alarm program detects issues before malfunction occurs.
- Digital display allows for easy monitoring.
- Sensitive touch display.

■ Ducted fan air distribution system

Maintains temperature within the food zone

■ On/Off switch

ON/OFF switch is located on control panel

■ All stainless steel cabinet construction

The PRO series model boasts a stainless steel interior and a **22 gauge** stainless steel exterior (galvanized steel top, bottom). It guarantees the utmost in cleanliness and long product life. The PRO series model adds a touch of style to the most refined setting.

■ Sturdy, clean stainless steel shelving

Shelves are the most important part of cleanliness as they come in direct contact with food. After a while, PVC coated wire shelves may peel, rust and lead to unsanitary conditions. Only the Turbo Air PRO series uniquely provides stainless steel shelving.

■ LED interior lighting

■ High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

■ Full length stainless steel solid doors with locks

■ Self-closing doors with stay open feature at 120 degrees

■ Heated cabinet holds 140°F ~ 180°F for the best in food preservation

■ Lifetime guaranteed heavy duty hinges and handles



Model	Swing Door	CU./FT.	#of Rack Accepted	Wattage (W)	AMPS	Crated Weight (lbs.)	L x D x H [†] (inches)
PRO-50H-RI	2	75.59	2	3000	15	696	667/8 x 373/4 x 841/4

Roll-In Solid Door Heated Cabinet

Roll-In
PRO Series

Model : PRO-50H-RI

ELECTRICAL DATA	
Voltage	208/115/60/1
Plug Type	☺ NEMA L14-20P
Full Load Amperes	15
Wattage (W)	3000
Feed Wires with Ground	4
Cord Length (ft.)	8
DIMENSIONAL DATA	
# of Doors	2
# of Racks Accepted	2
Net Capacity (cu. ft.)	75.59
Ext. Length Overall (in.)	66 7/8 (1700mm)
Ext. Depth Overall (in.)	37 3/4 (960mm)
Ext. Height Overall (in.)*	84 1/4 (2140mm)
Int. Length Overall (in.)	57 3/8 (1459mm)
Int. Depth Overall (in.)	31 1/2 (800mm)
Int. Height Overall (in.)	66 7/8 (1699mm)
Rack Size (L x D x H) (in.)	27 x 29 x 66
Net Weight (lbs.)	544
Gross Weight (lbs.)	696

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

* Depth does not include 1-1/4" for door handles. Depth does not include 5-1/2" for ramp.

■ WARRANTY : 3 Year Parts and Labor Warranty


■ STANDARD FEATURES

- Door locks standard
- Solid and sturdy grille design
- Heavy duty stainless steel ramp standard


** Lead time applies. Please contact your sales representative for more details to order.

PLAN VIEW

(unit : inch)



TOP VIEW



SIDE VIEW

Ver.20200420



- Turbo Air : 800-627-0032
- GK : 800-500-3519
- Warranty : 800-381-7770
- AC : 888-900-1002

REFRIGERATOR MANUFACTURER
Turbo air

GERMAN
KNIFE

||| **RADIANCE**

REFRIGERATION SYSTEM
Turbo air

texaking