

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project :		
Model #:		
Item #:	Qty:	
Available W/H :		
Approval :		

Top Open Island Freezer

Model: TFS-25F-N



___ FEATURES & BENEFITS =__

- Hydrocarbon refrigerants (R-290)
 - With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet the new standards of the EPA and DOE in 2017. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).
- 5 years Cleaning-free condenser
 - 1/5" condenser pin gaps and electrodeposition coating allow the condenser to stay clean and prevent it from becoming tarnished, further guaranteeing the durability of the condenser.
- High-density polyurethane insulation
 - The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.
- Horizontal display freezer for high impulse sales
 - Flat lid display freezer provides convenient access and fast service and is ideal for high impulse sales such as frozen treats. Minimal frame glass lids allow excellent visibility with maximum merchandising effect.
- Tempered, energy-saving, Low-E glass sliding top
 Energy saving Low-emissivity glass top reduces outer heat gain and
 lowers energy consumption. Reinforced tempered glass lids for safety.

- White, anti-rust coating on the exterior reduces fingerprints
- LED interior lighting with on/off switch
- External digital temperature control
- Painted white powder-coated steel interior
- Two layers of rubber bumper guards around the cabinet
- Manual defrost system with drain
- Wire baskets come standard
- Freezer holds -10°F ~ 8°F for the best in frozen food preservation











Model	Sliding Door	CU./FT.	#of Baskets	HP	AMPS	Crated Weight (lbs.)	L x D x H* (inches)
TFS-25F-N	2	25	33	1/2	4.6	520	69 x 311/2 x 311/4

Top Open Island Freezer

Model: TFS-25F-N

ELECTRICAL DATA					
Voltage	115/60/1				
Plug Type	(i) NEMA 5-15P				
Full Load Amperes	4.6				
Compressor HP	1/2				
Cord Length (ft.)	7				
Refrigerant	R-290				
DIMENSIONAL DATA					
# of Doors	2				
Net Capacity (cu. ft.)	25				
Net Capacity (Gal.)	188.7				
Ext. Length Overall (in.)	69 (1750mm)				
Ext. Depth Overall (in.)	31 _{1/2} (800mm)				
Ext. Height Overall (in.)*	31 _{1/4} (793mm)				
Int. Length Overall (in.)	635/8 (1614mm)				
Int. Depth Overall (in.)	261/8 (664mm)				
Int. Height Overall (in.)	237/8 (607mm)				
# of Baskets	33				
Net Weight (lbs.)	470				
Gross Weight (lbs.)	520				

Design and specifications subject to change without notice.


Actual shipping weight may differ due to extra packing materials for product protection.

2 Year Parts and Labor Warranty Additional 3 Year Warranty on Compressor

- Anti-corrosion coated evaporator
- No plumbing required
- Self-contained system
- 2.5" dia.casters standard, two locking
- Recommended operating conditions:


TFS models are designed to operate in air conditioned environments where temperature and humidity are below 75°F and 55% relative humidity. Place units away from direct sunlight, rapid air movement and extreme temperature changes


PLAN VIEW



(unit: inch)

TOP VIEW





Ver.20171030

NATURAL







■ **Turbo Air**: 800-627-0032 ■ **GK**: 800-500-3519

■ Warranty: 800-381-7770 ■ AC: 888-900-1002











^{*} Height does not include 3-1/2" for caster height.